



# PNG-200

PORTABLE NOISE GENERATOR

The PNG-200 is designed as a portable acoustic noise generating unit that can be used in a variety of ways. Single units can be used for noise masking to protect close proximity private conversations. When multiple units are used in concert, a complete masking system can be easily installed in any environment.

Multiple PNG-200 units can be quickly mounted to walls and windows for direct perimeter masking (similar to the ANG-2000 noise masking system) or simply scattered about to fill an environment with acoustic noise.

## Features

- Optimized voiceband noise masking for acoustic interference against listening devices (acoustic noise is tailored to voice frequencies.)
- Mounts easily to windows using suction cup (included) to defeat high tech laser threats
- Mounts easily to walls for protection against listening devices that rely on acoustic leakage (i.e. contact mics, spike mics, human ear)
- Multiple units fit in a briefcase designed for ruggedness and portability



## Technical Specifications

### SIZE:

5.38 in x 3.38 in x 1.25 in  
(13.67 mm x 8.59 mm x 3.18 mm)

### WEIGHT:

12 oz. (340.2 g)

### AUDIO FREQUENCY RANGE:

300Hz-3kHz

### OUTPUT SOUND LEVEL:

MAX 92dB @ 4 ft.

### POWER:

- Two 9V alkaline batteries; optional AC transformer (120 or 240VAC)
- Battery Life: typically 7 hrs. at 1/2 level; 2 hrs. at full level

### INCLUDES:

- Carrying case, AC transformer, and suction cup window/wall mounting kit

### STORAGE CASE



### ACCESSORIES



Portable kit of multiple units for temporary, complete room installation

